## **VTevo**

The lighting power of 4x290W LED floodlights meets a very narrow canopy design evolving the new VTevo onto the most compact and eco-friendly lighting tower ever created! VTevo will help you to skimp up to 75% of fuel and protect our environment with a reduction in carbon emissions up to 10 Ton per year. The machine can run continuously without refuelling up to 240 hours.





GENERAC® LED LAMPS
4x290 W high efficiency
LED floodlights designed by
Generac® Tower Light.



VTevo Y

TECHNICAL DATA			
Minimum dimensions (mm)	Lenght x Width x Height	2480 x 1310 x 2450	2480 x 1310 x 2450
Maximum dimensions (mm)	Lenght x Width x Height	2480 x 2400 x 8000	2480 x 2400 x 8000
Dry weight (kg)		658	640
Lifting system	M:Manual / H:Hydraulic	M	M
Mast rotation (°)		340	340
Lamps power (W)		4 x 290	4 x 290
Lamps type	MH:MetalHalide / LD:LED	LD	LD
Total lumen (Lm)		156000	156000
Illuminated area (m²)		3600	3600
Engine		Kubota Z482	Yanmar L70N
Engine cooling	W:water / A:air	W	A
Cylinders (q.ty)		2	1
Engine speed (RPM)	50 / 60 Hz	1500 / 1800	3000/3600
Liquid containment (110%)	√:Yes / •:No	$\checkmark$	√
Alternator	kVA/V/Hz	5/220/50 - 5/240/60	5/220/50 - 5/240/60
Outlet Socket	kVA/V/Hz	2/220/50 - 2/240/60	2/220/50 - 2/240/60
Avg. sound pressure	dB(A)@7mt	60	63
Wind speed resistance (km/h)		80	80
Tank capacity (liters)		120	120
Total running time (h)		200	240

VTevo K

## LIQUID CONTAINMENT TANK

A liquid containment tank to avoid any risk of leakages on the ground.

## ENVIRONMENTALLY FRIENDLY

Protect the environment with VTevo: reduced CO<sub>2</sub> emission up to 10 ton per year compared to a traditional light tower!



## **OPTIONS AVAILABLE**

- Low speed site-tow trailer (standard)
- Road trailer type A (straight)
- Road axle only
- Zinc coated skid base
- Pre-heating system
- Earth picket with 5m cable
- Certified spark arrestor

- Chalwyn valve
- Dedicated colour
- Second year of warranty
- Ball hitch type 50 mm
- Eyelet hitch type 50 mm
- Eco panel with digital timer and darkness sensor