


SKID STEERS

■ 2012 ■



mustangmfg.com

EXPAND options in small spaces



- A machine width as narrow as 36" with 5.70 x 12 chevron tire set, and 42" with 8.50 x 12 HD flotation tire set.

- A machine width as narrow as 3-feet with optional tires, a height of 6¼-feet and a length of 8½-feet, this unit is made for maneuvering in tight places where other machines can't gain access.



- Powered by a 24-hp Yanmar diesel engine the 2012 packs a load capacity of 850 lbs. for great performance in a small package.

- A machine shipping weight less than 2,900 lbs. makes for easy shipping and hauling
- An operator-friendly ROPS/FOPS Level II-certified cab keeps the operator comfortable all day long. A high-back, deluxe seat comes standard and a high-back suspension seat is available.



West Bend, WI USA
Tel: 262-334-9461
Fax: 262-338-7517

For more information on Mustang equipment, call our literature hotline at **800-628-0491** or visit our website: **mustangmfg.com**

A Per SAE J818, SAE J732, and ISO 14397
B Unit weight with standard bucket, 175 lbs. (79 kg) operator and full fuel tank

	2012	
DIMENSIONS	A. Overall Operating Height - Fully Raised (mm)	124.7" (3167)
	B. Height to Hinge Pin - Fully Raised (mm)	96" (2438)
	C. Overall Height to Top of ROPS (mm)	74.7" (1897)
	D. Ground Clearance to Chassis (mm)	5.9" (150)
	E. Overall Length with Bucket (mm)	101.4" (2576)
	F. Overall Length without Bucket (mm)	75" (1905)
	G. Wheelbase (mm)	30.5" (775)
	H. Dump Reach at Full Height (mm)	14.8" (376)
	I. Bucket Rollback at Ground	23.4°
	J. Dump Angle	46°
	K. Overall Width (mm)	35.8" (909)
	L. Bucket Width (mm)	36" (914)
	M. Clearance Circle - Rear (mm)	43.2" (1097)
	N. Clearance Circle - Front without Bucket (mm)	32.8" (833)
	O. Clearance Circle - Front with Bucket (mm)	58" (1473)
	P. Seat to Ground Height (mm)	34.6" (879)
	Q. Rollback at Full Height	61°
	R. Dump Height (mm)	72.3" (1836)
	S. Departure Angle	30°
Standard Specification Tire Size	5.70 x 12	
ENGINE	Make	Yanmar
	Model	3TNV82-Tier III
	Power (kW) @ rpm	24 hp (17.9) @2400
	Displacement (L)	81 cu.in. (1.33)
HYDRAULIC SYSTEM	Auxiliary Hydraulics - Standard (L/min)	9.1 gpm (34)
	Filtration	4 micron
	System Relief Pressure (bar)	2255 psi (155.5)
	Reservoir Capacity (L)	7.15 gal. (27.1)
CAPACITIES / WEIGHT	Rated Operating Capacity ^A (kg)	850 lbs. (385)
	Fuel Tank (L)	7.7 gal. (29)
	Travel Speed - Maximum (km/hr)	5.5 mph (8.9)
	Operating Weight ^B - Approximate (kg)	2980 lbs. (1352)

